

RF 543.1224USN 1/19/06

- 3 -

In the claims:

Please amend the claims as shown below:

1. (Original) A device for releasably mounting a bundle (30)  
5 of bags on a wall (2), said device comprising a wall-mounted  
suspension fitting (1), wherein one rear major surface of the  
bag bundle is connected to a sheet (40) which is parallel with  
said bundle and which is adapted for releasable co-action with  
the fitting (1), and wherein the bags (32) in said bundle are  
10 releasably (36) connected to said sheet at their respective  
opening regions, characterized in that the sheet has an  
opening (45) midway of its width; in that the fitting has an-  
upwardly directed clip-finger (11) which includes in an upper  
portion of its side facing towards the wall (2) a projection  
15 (15) that can be received in the opening (45) in the sheet  
(40); and in that the projection (15) has two vertically  
separated oblique surfaces (16,17) which are mutually  
convergent in a direction towards said wall for co-action with  
the upper and lower edges of the sheet opening.

20

2. (Original) A device according to claim 1, characterized in  
that the sheet (40) includes midway of its width a slot (43)  
which extends upwards from the lower edge (44) of the sheet  
and which has a horizontal width that is at least equally as  
25 large as the horizontal width of the projection (15) of the  
clip finger (15).

RF 543.1224USN 1/19/06

- 4 -

3. (Currently amended) A device according to claim 1 ~~or 2~~,  
characterized in that the lower end of the clip finger merges,  
via a web, with an upwardly directed clip leg (10) that is  
5 connectable to said wall (2).

4. (Original) A device according to claim 3, characterized in  
that the fitting is comprised of a springy, elastic strip-like  
element whose width corresponds to the width of the sheet  
10 opening (45) and the sheet slot (43) respectively.

5. (Currently amended) A device according to claim 3 ~~3-4~~,  
characterized in that the clip leg (10) carries on its outer  
surface discrete adhesive pads (20) for connection to the wall  
15 (2).

6. (Currently amended) A device according to claim 4 ~~any one~~  
~~of claims 4-5~~, characterized in that the upper end portion of  
the clip finger is curved downwardly and inwardly the clip leg  
20 (10) ~~such as~~ to form the projection (15).